



I L L I N O I S

---

UNIVERSITY OF ILLINOIS AT URBANA-CHAMPAIGN

-

PRODUCTION NOTE

University of Illinois at  
Urbana-Champaign Library  
Large-scale Digitization Project, 2007.



# UNIVERSITY OF ILLINOIS BULLETIN

ISSUED WEEKLY

Vol. XI

MARCH 16, 1914

No. 29

Entered as second-class matter Dec. 11, 1912, at the Post Office at Urbana, Ill., under the Act of Aug. 24, 1912.

---

## ACOUSTICS OF AUDITORIUMS

BY

F. R. WATSON



BULLETIN No. 73

ENGINEERING EXPERIMENT STATION

PUBLISHED BY THE UNIVERSITY OF ILLINOIS, URBANA

---

PRICE: TWENTY CENTS

EUROPEAN AGENT  
CHAPMAN AND HALL, LTD., LONDON

THE Engineering Experiment Station was established by act of the Board of Trustees, December 8, 1903. It is the purpose of the Station to carry on investigations along various lines of engineering and to study problems of importance to professional engineers and to the manufacturing, railway, mining, constructional, and industrial interests of the State.

The control of the Engineering Experiment Station is vested in the heads of the several departments of the College of Engineering. These constitute the Station Staff and, with the Director, determine the character of the investigations to be undertaken. The work is carried on under the supervision of the Staff, sometimes by research fellows as graduate work, sometimes by members of the instructional staff of the College of Engineering, but more frequently by investigators belonging to the Station corps.

The results of these investigations are published in the form of bulletins, which record mostly the experiments of the Station's own staff of investigators. There will also be issued from time to time in the form of circulars, compilations giving the results of the experiments of engineers, industrial works, technical institutions, and governmental testing departments.

The volume and number at the top of the title page of the cover are merely arbitrary numbers and refer to the general publications of the University of Illinois; *either above the title or below the seal is given the number of Engineering Experiment Station bulletin or circular, which should be used in referring to these publications.*

For copies of bulletins, circulars, or other information address the Engineering Experiment Station, Urbana, Illinois.

**This page is intentionally blank.**




FIG. 1. AUDITORIUM, UNIVERSITY OF ILLINOIS.

# UNIVERSITY OF ILLINOIS

## ENGINEERING EXPERIMENT STATION

---

BULLETIN No. 73

---



---

MARCH, 1914

---

### ACOUSTICS OF AUDITORIUMS.

BY F. R. WATSON, ASSISTANT PROFESSOR OF PHYSICS.

#### CONTENTS.

	Page
I. Introduction .....	3
Acknowledgment .....	5
II. Behavior of Sound Waves in a Room.....	5
III. Methods of Improving Faulty Acoustics.....	8
A. Reverberation and Its Cure.....	8
Experimental Work on Cure of Reverberation.....	9
Formulae for Reverberation of Sound in a Room.....	10
B. Echoes and Their Remedy.....	11
C. Popular Conception of Cures. Use of Wires and Sound- ing Boards .....	11
Sounding Boards .....	12
Modeling New Auditorium after Old Ones with Good Acoustics .....	12
D. The Effect of the Ventilation System on the Acoustics...	13
IV. The Investigation in the Auditorium at the University of Illinois .....	13
A. Preliminary Work .....	13
B. Details of the Acoustical Survey in the Auditorium.....	17
C. Conclusion Drawn from the Acoustical Survey.....	26
D. Methods Employed to Improve the Acoustics.....	26
Reflecting Boards .....	26
Sabine's Method .....	26
Method of Eliminating Echoes.....	29
Proposed Final Cure.....	29
V. Bibliography of Publications on Acoustics of Auditoriums...	31

**This page is intentionally blank.**



## ACOUSTICS OF AUDITORIUMS

### AN INVESTIGATION OF THE ACOUSTICAL PROPERTIES OF THE AUDITORIUM AT THE UNIVERSITY OF ILLINOIS.

#### I. INTRODUCTION.

Much concern has arisen in late years in the minds of architects because of the faulty acoustics that exist in many auditoriums. The prevalence of echoes and reverberations with the consequent difficulty in hearing and understanding on the part of the auditor defeats the purpose of the auditorium and diminishes its value.

The Auditorium at the University of Illinois presents such a case. The building is shaped nearly like a hemisphere, with several large arches and recesses to break up the regularity of its inner surface. The original plans of the architect were curtailed because of insufficient money appropriated for the construction. The interior of the hall, therefore, was built absolutely plain with almost no breaking up of the large, smooth wall surfaces; and, at first, there were no furnishings except the seats and the cocoa matting in the aisles. The acoustical properties proved to be very unsatisfactory. A reverberation or undue prolongation of the sound existed, and in addition, because of the large size of the room and the form and position of the walls, echoes were set up.

If an observer stood on the platform and clapped his hands, a veritable chaos of sound resulted. Echoes were heard from every direction and reverberations continued for a number of seconds before all was still again. Speakers found their utterances thrown back at them, and auditors all over the house experienced difficulty in understanding what was said. On one occasion the University band played a piece which featured a xylophone solo with accompaniment by the other instruments. It so happened that the leader heard the echo more strongly than the direct sound and beat time with it. Players near the xylophone kept time to the direct sound, while those farther away followed the echo. The confusion may well be imagined.

Thus it seemed that the Auditorium was doomed to be an acoustical horror; that speakers and singers would avoid it, and that auditors would attend entertainments in it only under protest. But the apparent misfortune was in one way a benefit since it provided an opportunity to




FIG. 2. PHOTOGRAPH OF INTERIOR. VIEW OF STAGE.




FIG. 3. PHOTOGRAPH OF INTERIOR. VIEW TOWARD BALCONY.

study defective acoustics under exceptionally good conditions and led to conclusions that not only allowed the Auditorium to be improved but also indicate some of the pitfalls to be avoided in future construction of other halls.

An investigation of the acoustical properties of the Auditorium was begun in 1908 and has continued for six years. It was decided at the outset not to use "cut and try" methods of cure, but to attack the problem systematically so that general principles could be found, if possible, that would apply not only to the case being investigated but to auditoriums in general. This plan of procedure delayed the solution of the problem, since it became necessary to study the theory of sound and carry out laboratory investigations at the same time that the complex conditions in the Auditorium were being considered. The author spent one year of the six abroad studying the theory of acoustics and inspecting various auditoriums.

The main echoes in the Auditorium were located by means of a new method for tracing the path of sound, the time of reverberation was determined by Sabine's method, and a general diagnosis of the acoustical defects was made. Hangings and curtains were installed in accordance with the results of the study so that finally the acoustical properties were improved.

*Acknowledgment.*—The author desires to express his great appreciation of the advice and encouragement given by President E. J. James, Supervising Architect J. M. White, and Professor A. P. Carman of the Physics Department. He desires also to acknowledge the material assistance cheerfully rendered by the workmen at the University, which contributed in no small degree to the successful solution of the problem,

## II. BEHAVIOR OF SOUND WAVES IN A ROOM.

When a speaker addresses an audience, the sounds he utters proceed in ever widening spherical waves until they strike the boundaries of the room. Here the sound is partly reflected, partly transmitted, and the rest absorbed. The amounts of reflection, absorption and transmission depend on the character of the walls. A hard, smooth wall reflects most of the sound so that but little is transmitted or absorbed. In the case of a porous wall or a yielding wall, the absorption and transmission are greater, and the reflection is less. After striking a number of reflecting surfaces, the energy is used up and the sound dies out.

The reflection of sound produces certain advantages and disadvantages for the acoustics. When it is considered that sound travels about 1100 feet a second it may be seen that a room of ordinary size is almost immediately filled with sound because of the many reflections. In a room 40 feet square, for instance, the number of reflections per second between opposite walls is  $1100 \div 40$ , or approximately 27. The number is really greater than this, since the sound that goes into the corners is reflected much more frequently than out in the middle where the distances between walls are greater. The result is that the sound mixes thoroughly in all parts of the room so as to give the same average intensity; that is, the sound is of the same average *loudness* for all auditors, even for those in the remotest corners.

Though the reflection of sound has the advantage of fulfilling the conditions for loudness, it introduces at the same time possibilities for setting up defective acoustics. For instance, when the walls of the room are hard and smooth very little energy is lost at each impact of the sound and many reflections take place before it finally dies out. This slow decadence of the sound, or *reverberation* as it is called, is the most common defect in auditoriums.

If a speaker talks in such a hall the auditors have difficulty in understanding. Each sound, instead of dying out quickly, persists for some time so that the succeeding words blend with their predecessors and set up a mixture of sounds which produces confusion. The cure for the trouble is brought about by the introduction of materials such as carpets, tapestries, and the like, which act as absorbers of sound and reduce the time of reverberation.

When music is played in an auditorium with a prolonged reverberation, the tones following one another blend and produce the same effect as that of a piano when played with the loud pedal in use. A reverberation is more advantageous for music than for speech, since the prolongation and blending of the musical tones is desired, but the mixing of the words in a speech is a distinct disadvantage. When curing this defect for halls used for both music and speaking, a middle course must be steered, so that the reverberation is made somewhat long for speaking and somewhat short for music, yet fairly satisfactory for both.

Going back to the consideration of the reflection of sound, it is found that another defect may be produced, namely, an *echo*. This is the case when a wall at some distance reflects the sound to the position of the auditor. He hears the sound first from the speaker, then later by reflec-

tion from the wall. The time interval between the direct and reflected sound must be great enough to allow two distinct impressions to be made. This time is about  $1/15$  of a second, but varies with the acuteness of the observer. The farther off the wall is, the greater is the time interval and the more pronounced is the echo. If the wall is not very distant, the time interval is too short to allow two distinct impressions to be made, and the effect on the auditor is then much the same as if his neighbor at his side speaks the words of the discourse in his ear at the same time that he gets them directly from the speaker. In case the reflecting wall is curved so as to focus the sound the echoes are much more pronounced. A curved wall wherever it may be placed in an auditorium is thus always a menace to good acoustics.

There are other actions of the sound that may result in acoustical defects. The phenomena of *resonance*, for instance, may cause trouble. Suppose that the waves of sound impinge on an elastic wall, not too rigid. If these waves are timed right they set the wall in vibration in the same way that the bell ringer causes a bell to ring by a succession of properly timed pulls on the bell rope. The wall of the room will then vibrate under the action of this sound with which it is in tune and will reinforce it. Now suppose a band is playing in a room. Certain tones are reinforced, while the others are not affected. The original sound is then distorted. The action is the same on the voice of the speaker. The sounds he utters are complex and as they reach the walls certain components are reinforced and the quality of the sound is changed. This action of resonance may also be caused by the air in a room. Each room has a definite pitch to which it responds, the smaller the volume of the room the higher being the pitch. A large auditorium would respond to the very low pitch of the bass drum. In small rooms and alcoves the response is made to higher pitched tones, as may be observed by singing the different notes of the scale until a resonance is obtained.

Another action of sound causes the *interference* of waves. Thus the reflected waves may meet the oncoming ones and set up concentrations of sound in certain positions and a dearth of sound in others.

Summing up, it is seen that the effects of sound which may exist in a room are *loudness*, *reverberation*, *echoes*, *resonance*, and *interference*, and that the most common defects are reverberation and echoes. We now turn to the discussion of the methods of cure.

## III. METHODS OF IMPROVING FAULTY ACOUSTICS.

## A. REVERBERATION AND ITS CURE.

Everyone has doubtless observed that the hollow reverberations in an empty house disappear when the house is furnished. So, in an auditorium, the reverberation is lessened when curtains, tapestries, and the like are installed in sufficient numbers. The reason for this action is found when we inquire what ultimately becomes of the sound.

Sound is a form of energy and energy can not be destroyed. When it finally dies out, the sound must be changed to some other form of energy. In the case of the walls of a room, for instance, it has been shown in a preceding paragraph that the sound may be changed into mechanical energy in setting these walls in vibration. Again, some of the sound may pass out through open windows and thus disappear. The rest of the sound, according to Lord Rayleigh, is transformed by friction into heat. Thus<sup>1</sup> a high pitched sound, such as a hiss, before it travels any great distance is killed out by the friction of the air. Lower pitched sounds, on reaching a wall, set up a friction in the process of reflection between the air particles and the wall so that some of the energy is converted into heat.<sup>2</sup> The amount of sound energy thus lost is small if the walls are hard and smooth. The case is much different, however, if the walls are rough and porous, since it appears that the friction in the pores dissipates the sound energy into heat. In this connection, Lamb<sup>3</sup> writes: "In a sufficiently narrow tube the waves are rapidly stifled, the mechanical energy lost being of course converted into heat. \* \* \* \*"

When a sound wave impinges on a slab which is permeated by a large number of very minute channels, part of the energy is lost, so far as the sound is concerned, by dissipation within these channels in the way just explained. The interstices in hangings and carpets act in a similar manner, and it is to this cause that the effect of such appliances in deadening echoes in a room is to be ascribed, a certain proportion of the energy being lost at each reflection. It is to be observed that it is only through the action of true dissipative forces, such as viscosity and thermal conduction, that sound can die out in an enclosed space, no mere modifications of the waves by irregularities being of any avail."

It should be pointed out in this connection that any mechanical breaking up of the sound by relief work on the walls or by obstacles in the room will not primarily diminish the energy of the sound. These

---

1. "Theory of Sound," Vol. II, p. 316.

2. "Theory of Sound," Vol. II, § 351.

3. "Dynamical Theory of Sound," p. 196.

may break up the regular reflection and eliminate echoes, but the sound energy as such disappears only when friction is set up.

The following quotation from Rayleigh<sup>1</sup> emphasizes these conclusions: "In large spaces, bounded by non-porous walls, roof, and floor, and with few windows, a prolonged resonance seems inevitable. The mitigating influence of thick carpets in such cases is well known. The application of similar material to the walls and roof appears to offer the best chance of further improvement."

*Experimental Work on Cure of Reverberation.*—The most important experimental work in applying this principle of the absorbing power of carpets, curtains, etc., has been done by Professor Wallace C. Sabine of Harvard University.<sup>2</sup> In a set of interesting experiments lasting over a period of four years, he was able to deduce a general relation between  $t$ , the time of reverberation,  $V$ , the volume of the room, and  $a$ , the absorbing power of the different materials present. Thus:

$$t = 0.164 V \div a \quad (1)$$

For good acoustical conditions, that is, for a short time of reverberation, the volume  $V$  should be small and the absorbing materials, represented by  $a$ , large. This is the case in a small room with plenty of curtains and rugs and furniture. If, however, the volume of the room is great, as in the case of an auditorium, and the amount of absorbing materials small, a troublesome reverberation will result.

Professor Sabine determined the absorbing powers of a number of different materials. Calling an open window a perfect absorber of sound, the results obtained may be written approximately as follows:

One square meter of open window space.....	1.000
One square meter of glass, plaster, or brick.....	.025
One square meter of heavy rugs, curtains, etc. ....	.25
One square meter of hair felt, 1 inch thick.....	.75
One square meter of audience .....	.96

These values, together with the formula, allow a calculation to be made in advance of construction for the time of reverberation. This pioneer work cleared the subject of architectural acoustics from the fog of mystery that hung over it and allowed the essential principles to be seen in the light of scientific experiment.

In a later investigation<sup>3</sup> Sabine showed that the reverberation depended also on the pitch of sound. As a concrete example, the high

1. "Theory of Sound," p. 333.

2. "Architectural Acoustics." A series of articles in the Engineering Record, 1900; also the American Architect, 1900.

3. "Architectural Acoustics," Proc. of Amer. Acad. of Arts and Sciences. Vol. 42, pp. 49-84, 1906.



notes of a violin might be less reverberant with a large audience than the lower tones of the bass viol, although both might have the same reverberation in the room with no audience. Again, the voice of a man with notes of low pitch might give satisfactory results in an auditorium while the voice of a woman with higher pitched notes would be unsatisfactory.

These considerations show that the acoustics in an auditorium vary with other factors than the volume of the room and the amount of absorbing material present. The audience may be large or small, the speaker's voice high or low, the entertainment a musical number or an address. The best arrangement for good acoustics is then a compromise where the average conditions are satisfied. The solution offered by Professor Sabine is such an average one, and has proved satisfactory in practice.

The problem of architectural acoustics has been attacked experimentally by other workers. Stewart<sup>1</sup> proposed a cure for the poor acoustical conditions in the Sibley Auditorium at Cornell University. His experiments confirmed the work of Sabine. Marage<sup>2</sup>, after investigating the properties of six halls in Paris, approved Sabine's results and advocated a time of reverberation of from  $\frac{1}{2}$  to 1 second for the case of speech.

*Formulae for Reverberation of Sound in a Room.*—On the theoretical side, Sabine's formula has been developed by Franklin,<sup>3</sup> who obtained the relation  $t = 0.1625 V \div a$ , an interesting confirmation, since Sabine's experimental value for the constant was 0.164.

A later development has been given by Jäger,<sup>4</sup> who assumes for a room whose dimensions are not greater than about 60 feet, that the sound, after filling the room, passes equally in all directions through any point, and that the average energy is the same in different parts of the room. By using the theory of probability and considering that a beam of sound in any direction may be likened to a particle with a definite velocity, he was able to deduce Sabine's formula and write down the factors that enter into the constants. Applying his results to the case of reflection of sound from a wall, he showed that sound would be reflected in greater volume when the mass of the wall was increased and

1. G. W. Stewart. "Architectural Acoustics," Sibley Journal of Engineering, May, 1903. Published by Cornell University, Ithaca, N. Y.

2. "Qualités acoustiques de certaines salles pour la voix parlée." Comptes Rendus, 142, 878, 1906.

3. W. S. Franklin. "Derivation of Equation of Decaying Sound in a Room and Definition of Open Window Equivalent of Absorbing Power." Physical Review, Vol. 16, pp. 372-374, 1908.

4. G. Jäger. "Zur Theorie des Nachhalls." Sitzungsberichte der Kaiserliche Akad. der Wissenschaften in Wien, Math-naturw. Klasse; Bd. CXX. Abt. 11 a. Mai, 1911.



the pitch of the sound made higher. He showed also that when sound impinges on a porous wall, more energy is absorbed when the pitch of the sound is high than when it is low, since the vibrations of the air are more frequent, and more friction is introduced in the interstices of the material.

#### B. ECHOES AND THEIR REMEDY.

An echo is set up by a reflecting wall. If an observer stands some distance from the front of a cliff and claps his hands, or shouts, he finds that the sound is returned to him from the cliff as an echo. So, in an auditorium, an auditor near the speaker gets the sound first directly from the speaker, then, an instant later, a strong repetition of the sound by reflection from a distant wall. This echo is more pronounced if the wall is curved and the auditor is at the point where the sound is focused.

To cure such an echo, two methods may be considered. One method consists in changing the form of the wall so that the reflected sound no longer sets up the echo. That is, either change the angle of the wall, so that the reflected sound is sent in a new direction where it may be absorbed or where it may reinforce the direct sound without producing any echoes, or else modify the surface of the wall by relief work or by panels of absorbing material, so that the strong reflected wave is broken up and the sound is scattered. The second method is to make the reflecting wall a "perfect" absorber, so that the incident sound is swallowed up and little or none reflected. These methods have been designated as "surgical" and "medicinal" respectively. Each method has its disadvantages. Changing the form of the walls in an auditorium is likely to do violence to the architectural design. On the other hand, there are no perfect absorbers, except open windows, and these can seldom be applied. The cure in each case is, then, a matter of study of the special conditions of the auditorium. Usually a combination of the surgical and the medicinal cures is adopted. For instance, coffering a wall so that panels of absorbing material may be introduced has been found to work well in bettering the acoustics, and also, in many cases, it fits in with the architectural features.

#### C. POPULAR CONCEPTION OF CURES.—USE OF WIRES AND SOUNDING BOARDS.

A few words should be written concerning the popular notion that wires and sounding boards are effective in curing faulty acoustics. Experiments and observations show that wires are of practically no

benefit, and sounding boards can be used only in special cases. Wires stretched in a room scarcely affect the sound, since they present too small a surface to disturb the waves. They have much the same effect on sound waves that a fish line in the water has on water waves. The idea has, perhaps, grown into prominence because of the action of a piano in responding to the notes of a singer. The piano has every advantage over a wire in an auditorium. It has a large number of strings tuned to different pitches so that it responds to any note sung. It also has a sounding board that reinforces strongly the sound of the strings. Finally, the singer is usually near the piano. The wire in the auditorium responds to only one tone of the many likely to be present, it has no sounding board, and the singer is some distance away. But little effect, therefore, is to be expected.

The author has visited a number of halls where wires have been installed, and has yet to find a case where pronounced improvement has resulted.<sup>1</sup> Sabine<sup>2</sup> cites a case where five miles of wire were stretched in a hall without helping the acoustical conditions. It is curious that so erroneous a conception has grown up in the public mind with so little experimental basis to support it.

*Sounding Boards.*—Sounding boards or, more properly, reflecting boards, have value in special cases. Some experiments are described later where pronounced effects were obtained. The sounding board should be of special design to fit the conditions under which it is to be used.

*Modeling New Auditoriums after Old Ones with Good Acoustics.*—Another suggestion often made is for architects to model auditoriums after those already built that have good acoustical properties. It does not follow that halls so modeled will be successful, since the materials used in construction are not the same year after year. For instance, a few years ago it was the usual custom to put lime plaster on wooden lath; now it is frequently the practice to put gypsum plaster on metal lath, which forms an entirely different kind of a surface. This latter arrangement makes hard, non-porous walls which absorb but little sound, and thus aggravate the reverberation. Further, a new hall usually is changed somewhat in form from the old one, to suit the ideas of the architect, and it is very likely that the changes will affect the acoustics.

---

1. Science, Vol. 35, p. 833, 1912.

2. Arch. Quarterly of Harvard University, March, 1912.

#### D. THE EFFECT OF THE VENTILATION SYSTEM ON THE ACOUSTICS.

At first thought it might seem that the ventilation system in a room would affect the acoustical properties. The air is the medium that transmits the sound. It has been shown that the wind has an action in changing the direction of propagation of sound.<sup>1</sup> Sound is also reflected and refracted at the boundary of gases that differ in density and temperature.<sup>2</sup> It is found, however, that the effect of the usual ventilation currents on the acoustics in an auditorium is small. The temperature difference between the heated current and the air in the room is not great enough to affect the sound appreciably, and the motion of the current is too slow and over too short a distance to change the action of the sound to any marked extent.<sup>3</sup>

Under special circumstances, the heating and ventilating systems may prove disadvantageous.<sup>4</sup> A hot stove or a current of hot air in the center of the room will seriously disturb the action of sound. Any irregularity in the air currents so that sheets of cold and heated air fluctuate about the room will also modify the regular action of the sound and produce confusion. The object to be striven for is to keep the air in the room as homogeneous and steady as possible. Hot stoves, radiators, and currents of heated air should be kept near the walls and out of the center of the room. It is of some small advantage to have the ventilation current go in the same direction that the sound is to go, since a wind tends to carry the sound with it.

### IV. THE INVESTIGATION IN THE AUDITORIUM AT THE UNIVERSITY OF ILLINOIS.

#### A. PRELIMINARY WORK.

As already stated, a chaos of sound was set up when an observer in the Auditorium spoke or shouted or clapped his hands. Both echoes and reverberations were present and could be heard in all parts of the room, though the echoes seemed to be strongest on the stage and in the balcony. The prospects for bettering the acoustics were not very encouraging. Luckily, the cure for the reverberation was fairly simple, since Sabine's method gave a definite procedure that could be applied to this case. The cure for the echo, however, was yet to be found. It was first necessary to find out which walls set up the defect.

1. Osborne Reynolds. *Proc. of Royal Soc.*, Vol. XXII, p. 531, 1874.

2. Joseph Henry, "Report of the Lighthouse Board of the United States for the year 1874."

J. Tyndall, *Phil. Trans.*, 1874.

3. Sabine, *Engineering Record*, Vol. 61, p. 779, 1910.

Watson, *Engineering Record*, Vol. 67, p. 265, 1913.

4. Sabine and Watson. *Ibid.*

The attempt to locate echoes by generating a sound and listening with the ear met with only partial success. The ear is sensitive enough but becomes confused when many echoes are present, coming apparently from every direction, so that the evidence thus obtained is not altogether conclusive. It became apparent that the successful solution lay in fixing the attention on the sound going in a particular direction and finding out where it went after reflection; then tracing out the path in another particular direction, and so on until the evidence obtained gave some hint of the general action of the sound.




FIG. 4. WATCH AS SOURCE OF SOUND, BACKED BY A CONCAVE REFLECTOR.

The first step in the application of this principle was to use a faint sound which could not be heard at any great distance unless reinforced in some way. The ticks of a watch were directed, by means of a reflector (Fig. 4) to certain walls suspected of giving echoes. Using the relation that the angle of incidence equals the angle of reflection, the reflected sound was readily located, and the watch ticks heard distinctly after they had traveled a total distance as great as 70 to 80 feet from the source.

In a later experiment, a metronome was used which gave a louder sound. It was enclosed in a sound-proof structure (Fig. 5) with only one opening, so that the sound could be directed by means of a horn. This method was suggested by the work of Gustav Lyon in the Hall of the Trocadero at Paris,\* where a somewhat similar arrangement was used. The method was successful and verified the observations taken previously.

\*La Nature (Paris), April 24, 1909.




FIG. 5. METRONOME AS SOURCE OF SOUND.

Though the results obtained with the watch and metronome seemed conclusive, yet the observer was not always confident of the results. A further method was sought, and a more satisfactory one found by using an alternating current arc-light at the focus of a parabolic reflector (Fig. 6). In addition to the light, the arc gave forth a hissing sound, which was of short wave length and therefore experienced but little diffraction. The bundle of light rays was, therefore, accompanied by a bundle of sound, both coming from the same source and




FIG. 6. ARC-LIGHT AS SOURCE OF SOUND.

subject to the same law of reflection. The path of the sound was easily found by noting the position of the spot of light on the wall. The reflected sound was located by applying the relation that the angles of incidence and reflection are equal. The arc-light sound was intense and gave the observer confidence in results that was lacking in the other

methods. To trace successive reflections, small mirrors were fastened to the reflecting walls so that the path of the reflected sound was indicated by the reflected light. A "diagnosis" of the acoustical troubles of the Auditorium was then made by this method.

It should be noted here that the arc-light sound is not the same as the sounds of music or speech, these latter ones being of lower pitch and of longer wave length. It was, therefore, a matter of doubt whether the results obtained would hold also for the case of speech or music. Tests made by observers stationed in the Auditorium when musical numbers and speeches were rendered, however, verified the general conclusions obtained with the arc-light.

It should be pointed out in this connection that there is an objection to applying the "ray" method of geometrical optics to the case of sound. It is much more difficult to get a ray of sound than it is to get a ray of light.\* This is due to the difference in the wave lengths in the two cases. It appears that the waves are diffracted, or spread out, in proportion to their length, the longer waves being spread out to a greater extent. The short waves of light from the sun, for instance, as they come through a window mark out a sharp pattern on the floor, which shows that the waves proceed in straight lines with but little diffraction or spreading. Far different is it with the longer waves of sound. If the window is open, we are able to hear practically all the sounds from outdoors, even that of a wagon around the corner, although we may be at the other end of the room away from the window. The longer sound waves spread out and bend at right angles around corners, so that it is almost impossible to get a sound shadow with them. Furthermore, in the matter of reflection, it appears that the area of the reflecting wall must be comparable with the length of the waves being reflected. In the case of light, the waves are very minute, hence a mirror can be very small and yet be able to set up a reflection; but sound waves are of greater length, the average wave length of speech (45 cm.) being about 700 000 times longer than the wave length of yellow light (.00006 cm.), hence the reflecting surface must be correspondingly larger. An illustration will perhaps make this clearer. Suppose a post one foot square projects through a water surface. The small ripples on the water will be reflected easily from the post, but the large water waves pass by almost as if the post were not there. The reflecting surface must have an area comparable with the size of the wave if it is to cause an effective reflection. Relief work in auditoriums, if of small dimensions, will affect only the high pitched sounds, i. e., those of short wave length, while the low

---

\*Rayleigh "Theory of Sound," Vol. II, § 283.

pitched sounds of long wave length are reflected much the same as from a rather rough wall. It is also shown that the area of the reflecting surface is dependent on its distance from the source of sound and from the observer; the greater these distances are the larger must be the reflecting surface.\*

These considerations all show that the reflection of sound is a complicated matter. The dimensions of a wall to reflect sound, or of relief work to scatter it, are determined by the wave length and by the various other factors mentioned. It should be said with caution that a "ray" of sound is reflected in a definite way from a small bit of relief work. We must deal with *bundles* of sound, not too sharply bounded, and have them strike surfaces of considerable area in order to produce reflections with any completeness.




FIG. 7. LONGITUDINAL SECTION SHOWING THE CHIEF CONCENTRATIONS OF SOUND, THE DIFFRACTION EFFECTS BEING DISREGARDED.

#### B. DETAILS OF THE ACOUSTICAL SURVEY IN THE AUDITORIUM.

The general effect of the walls of the Auditorium on the sound may be anticipated by considering analogous cases in geometrical optics, but with the restrictions on "rays" described in the preceding paragraph. The sound does not actually confine itself to the sharp boundaries shown. The diagrams are intended to indicate the main effect of the sound in the region so bounded. Fig. 7 gives such an idea for the concentration of sound in the longitudinal section of the Auditorium.

\*Rayleigh, *ibid*, 283.

The plan followed in the experimental work was to anticipate the path of the sound as indicated in Fig. 7, then to verify the results with the arc-light reflector. Figs. 8 and 9 show the effect of the rear wall in the balcony in forming echoes on the stage. The speaker was particularly unfortunate, being afflicted with no less than ten echoes.




FIG. 8. LONGITUDINAL SECTION SHOWING HOW SOUND IS RETURNED TO THE STAGE TO FORM AN ECHO.




FIG. 9. LONGITUDINAL SECTION SHOWING FORMATION OF ECHO ON THE STAGE.

The hard, smooth, circular wall bounding the main floor under the balcony gave echoes as shown in Fig. 10, the sound going also in the reverse direction of the arrows.






FIG. 10. PLAN OF AUDITORIUM SHOWING ACTION OF REAR WALL ON THE SOUND.




FIG. 11. PLAN OF AUDITORIUM SHOWING CONCENTRATION OF SOUND BY THE REAR WALL.




FIG. 12. THIS FIGURE TAKEN WITH FIG. 9 SHOWS HOW AN ECHO IS SET UP ON THE STAGE.

A more comprehensive idea of the action of this wall is shown in Fig. 11. This reflected sound was small in amount and therefore not a serious disadvantage.

The cases cited were fairly easy to determine since the bundles of sound considered were confined closely to either a vertical or a horizontal plane for which the plans of the building gave some idea of the probable path of the sound. For other planes, the paths followed could be anticipated by analogy from the results already found. Fig. 12 shows in perspective the development of the result expressed in Fig. 9.

A square bundle of sound starts from the stage and strikes the spherical surface of the dome. After reflection, it is brought to a point focus, as shown, and spreads out until it strikes the vertical cylindrical wall in the rear of the balcony. This wall reflects it to a line focus, after which it proceeds to the stage. Auditors on all parts of the stage complained of hearing echoes.

Referring to Fig. 7, it is seen that the arch over the stage reflects sound back to the stage. Fig. 13 shows in perspective the focusing action of this overhead arch. Fig. 14 shows the effect of the second arch.




FIG. 13. PERSPECTIVE OF STAGE SHOWING FOCUSING ACTION OF ARCH ON SOUND.

Some of this sound is reflected to the stage and to the seats in front of the stage; other portions, striking more nearly horizontally, are reflected to the side balconies. The echoes are not strong except for high pitched notes with short wave lengths, since the width of the arch is small.

Passing now to the transverse section, Fig. 15, we find the most pronounced echoes in the Auditorium. If an observer generates a sound in the middle of the room directly under the center of the skylight, distinct echoes are set up. A bundle of sound passes to the concave surface which converges the sound to a focus, after which it spreads out again to the other concave surface and is again converged to a focus




FIG. 14. PERSPECTIVE OF STAGE SHOWING FOCUSING ACTION OF SECOND ARCH




FIG. 15. TRANSVERSE SECTION SHOWING HOW MOST PRONOUNCED ECHOES ARE SET UP BY THE TWO CONCAVE SURFACES.

nearly at the starting point. The distance traveled is about 225 feet, taking about  $\frac{1}{4}$  second, so that the conditions are right for setting up a strong echo. This echo is duplicated by the sound which goes in the reverse of the path just described. Another echo, somewhat less strong, is formed by the sound that goes to the dome overhead and which is reflected almost straight back, since the observer is nearly at the center of the sphere of which the dome is a part. These echoes repeat themselves, for the sound does not stop on reaching the starting point but is reflected from the floor and repeats the action just described. As many as ten distinct echoes have been generated by a single impulse of sound.




FIG. 16. ACTION OF SOUND IN CAUSING ECHO ON THE STAGE.

The echo shown in Fig. 15 is repeated in a somewhat modified form for a sound generated on the stage by a speaker. Fig. 16 shows the path taken by the sound. This echo is duplicated by the sound that goes in the reverse direction of the arrows, so the speaker is greeted from

both sides. Fig. 17 is a perspective showing the path. The sound does not confine itself closely to a geometrical pattern, as shown in the picture, but spreads out by diffraction. The main effect is shown by the figure.




FIG. 17. PERSPECTIVE SHOWING HOW AN ECHO IS FORMED ON THE STAGE BY TWO REFLECTIONS. DIFFRACTION EFFECTS ARE NOT CONSIDERED IN THIS DRAWING.

Thus far only the echoes that reached the stage have been described. Other echoes were found in other parts of the hall, and it seemed that few places were free from them. The side walls in the balcony, for instance, were instrumental in causing strong echoes in the rear of the balcony. Fig. 18 shows in perspective the action of one of these walls. These two surfaces were similar in shape and symmetrically placed. Each was the upper portion of a concave surface with its center of curvature in the center of the building under the dome. The general effect of the left hand wall was to concentrate the sound falling on it

in the right hand seats in the balcony. Some of the sound struck the opposite wall and was reflected to the stage, as shown in Fig. 17. Auditors who sought the furthestmost rear seats in the balcony to escape echoes were thus caught by this unexpected action of the sound. The right hand wall acted in a similar way to send the sound to the upper left balcony.




FIG. 18. PERSPECTIVE SHOWING SOUND REFLECTED FROM CONCAVE WALL IN BALCONY. DIFFRACTION NOT CONSIDERED.

The dome surface concentrates most of its sound near the front of the central portion of the balcony and the ground floor in front of the balcony in the form of a caustic cone. Figs. 7, 9 and 11 give some conception of how a concentration of sound is caused by this spherical surface. The echo in the front portion of the balcony was especially distinct. On one occasion, in this place, the author was able to hear the speaker more clearly from the echo than by listening to the direct sound.

Minor echoes were set up by the horizontal arch surfaces in the balcony. The sound from the stage was concentrated by reflection from these surfaces and then passed to a second reflection from the concave surfaces back of them. Auditors in the side balcony were thus disagreeably startled by having sound come from overhead from the rear.

#### C. CONCLUSION DRAWN FROM THE ACOUSTICAL SURVEY.

The results of the survey show that curved walls are largely responsible for the formation of echoes because they concentrate the reflected sound. It seems desirable, therefore, to emphasize the danger of using such walls unless their action is annulled by absorbing materials or relief work. Large halls with curved walls are almost sure to have acoustical defects.

#### D. METHODS EMPLOYED TO IMPROVE THE ACOUSTICS.

*Reflecting Boards.*—The provisional cure was brought about gradually by trying different devices suggested by the diagnosis. In one set of experiments sounding boards of various shapes and sizes were used. A flat board about five feet square placed at an incline over the position of the speaker produced little effect. A larger canvas surface, about 12 by 20 feet, was not much better. A parabolic reflector, however, gave a pronounced effect. This reflector was mounted over a pulpit at one end of the stage and served to intercept much of the sound that otherwise would have gone to the dome and produced echoes. The path of the reflected sound was parallel to the axis of the paraboloid of which the reflector was a quarter section. There was no difficulty in tracing out the reflected sound. Auditors in the path of the reflected rays reported an echo, but auditors in other parts of the Auditorium were remarkably free from the usual troubles. The device was not used permanently, since many speakers objected to the raised platform. Moreover, it was not a complete cure, since it was not suited for band concerts and other events, where the entire stage was used. Another reflector similar in shape to the one just described is shown in Figs. 21 and 22.

*Sabine's Method.*—The time of reverberation was determined by Sabine's method. An organ pipe making approximately 526 vibrations a second was blown for about three seconds and then stopped. An auditor listened to the decreasing sound, and when it died out made a record electrically on a chronograph drum. The time of reverberation was found to be 5.90 seconds, this being the mean of 19 sets of measurements, each of about 20 observations. The reverberation was found also by calculation from Sabine's equation (see Section III), taking the volume of the Auditorium as 11 800 cubic meters and calculating the






FIG. 19. REFLECTING BOARD IN PROCESS OF CONSTRUCTION.




FIG. 20. FINISHED REFLECTOR. HARD PLASTER ON WIRE LATH.




FIG. 21. PARABOLIC REFLECTOR SHOWING ITS ACTION ON SOUND.




FIG. 22. PHOTOGRAPH OF PARABOLIC REFLECTOR.

absorbing power of all the surfaces in the room. This calculation gave 6.4 seconds. The agreement between the two results is as close as could be expected, since neither the intensity of the sound nor the pitch used by the author was the same as those used by Professor Sabine, and both of these factors affect the time of reverberation.

Several years later the time of reverberation was again determined after certain changes had been made. A thick carpet had been placed on the stage, heavy velour curtains 18 by 32 feet in area hung on the wall at the rear of the stage, a large canvas painting 400 square feet in area was installed, and the glass removed from the skylight in the ceiling. The time of reverberation was reduced to 4.8 seconds. With an audience present this value was reduced still more, and when the hall was crowded at commencement time the reverberation was not troublesome.

*Method of Eliminating Echoes.*—Although the time of reverberation was reduced to be fairly satisfactory, as just explained, the echoes still persisted, and were very annoying. Attempts were made to reduce individual echoes by hanging cotton flannel on the walls at critical points. Thus the shaded areas in Fig. 17 were covered and also the entire rear wall in the balcony. Pronounced echoes still remained, and it was evident that some drastic action was necessary to alleviate this condition. Four large canvases, shown in Figs. 23 and 24, were then hung in the dome in position suggested by the results of the diagnosis. A very decided improvement followed. For the first time the echoes were reduced to a marked degree and speakers on the stage could talk without the usual annoyance. This arrangement eliminated the echoes not only on the stage, but generally all over the house. A number of minor echoes were still left, but the conditions were much improved, especially when a large audience was present to reduce the reverberation.

*Proposed Final Cure.*—The state of affairs just described is the condition at the time of writing. Two propositions were considered in planning the final cure. One proposition involved a complete remodeling of the interior of the Auditorium. Plans of an interior were drawn in accordance with the results of the experimental work that would probably give satisfactory acoustics. This proposition was not carried out because of the expense and because it was thought desirable to attempt a cure without changing the shape of the room. The latter plan is the one now being followed. It is proposed to replace the present unsightly curtains with materials which will conform to the architectural features of the Auditorium and which will have a pleasing color scheme. At the same time, it will be necessary to hold to the features which have improved the acoustics.




FIG. 23. PHOTOGRAPH OF TWO OF THE CANVAS CURTAINS IN THE DOME OF THE AUDITORIUM. NOTE ALSO THE ABSORBING MATERIALS UNDER THE ARCHES.




FIG. 24. PHOTOGRAPH OF DOME OF AUDITORIUM SHOWING THE CANVASES INSTALLED TO ELIMINATE ECHOES.

## V. BIBLIOGRAPHY OF PUBLICATIONS ON ACOUSTICS OF AUDITORIUMS.

- Auerbach, F.* "Akustik." Winkelmann's Handbuch der Physik, Vol. II, 1909. An encyclopædia of acoustics, the following topics applying to the subject in hand: "Akustik der Gebäude," pp. 580-584, with references. "Nachhall und Echo," pp. 565-569, with references.
- Blackall, C. H.* "Acoustics of Audience Halls," Engineering Record, Vol. 45, pp. 541-542, 1902. A paper recording the opinions of the author with many references to acoustical properties of particular audience halls.
- Cornelison, R. W.* "The Acoustical Properties of Rooms Particularly as Affected by Wall Coverings," 1905. A pamphlet describing the merits of "Fabrikona" burlap as a sound absorber. H. B. Wiggin's Sons Company, Bloomfield, N. J.
- Eichhorn, A.* "Die Akustik Grosser Räume nach Altgriechischer Theorie." Ernst und Korn, Publishers, Berlin, 1888. A discussion of Greek buildings and acoustics, with applications to modern conditions.
- Eichhorn, A.* "Der Akustische Masstab für die Projectbearbeitung Grosser Innen Räume." Published by Schuster and Bußeb, Berlin, 1899. A continuation of the previous work.
- Erner, S.* "Über die Akustik von Hörsälen und ein Instrument, sie zu bestimmen." Zeitschrift des Österreichischen Ingenieur und Architekten-Vereines, Vol. LVII, p. 141, March, 1905. Indicates his opinion of good acoustical properties in a hall. Gives experimental determination of reverberation.
- Fournier, Lucien.* "The Suppression of Echoes." La Nature (Paris), April 24, 1909. English translation given in "The Literary Digest," New York, May 29, 1909, p. 924. An account of the experiments of Gustav Lyon in investigating the echoes in Trocadero Hall in Paris.
- Franklin, W. S.* "Derivation of Equation of Decaying Sound in a Room and Definition of Open Window Equivalent of Absorbing Power." Physical Review, Vol. 16, pp. 372-374, 1903. A theoretical development of the formula found experimentally by Sabine.
- Haage.* "Bemerkungen über Akustik." Zeitschrift für Baumesen, Vol. IX, pp. 582-594, 1859.
- Henry, Joseph.* "Acoustics Applied to Public Buildings," Smithsonian Report, 1856, p. 221.
- Hoyt, J. T. N.* "The Acoustics of the Hill Memorial Hall," American Architect, Vol. CIV, pp. 50-53, August 6, 1913. Discusses the design of the hall and indicates how it fulfills his ideas of good acoustics.
- Hutton, W. R.* "Architectural Acoustics; Hall of Representatives, U. S. Capitol, 1853." Engineering Record, Vol. 42, p. 377, 1900. A discussion of the cure of the faulty acoustics in the U. S. Hall of Representatives.
- Jacques, W. W.* "Effect of the Motion of the Air Within an Auditorium Upon Its Acoustical Qualities." Philosophical Magazine (5), Vol. 7, p. III, 1879. A record of experiments in the Baltimore Academy of Music showing that the ventilating current had a marked action on the acoustics.
- Jäger, S.* "Zur Theorie des Nachhalls," Sitzungsberichten der Kaiserl. Akademie der Wissenschaften in Wien. Matem.-naturw. Klasse; Bd. CXX, Abt. Ha, Mai, 1911. An important paper giving a theoretical development of Sabine's formula showing the factors that enter into the constants. Considers also the case of the reflection of sound from a thin wall and also the case when it encounters a porous material such as a curtain.
- Lamb, Horace.* "The Dynamical Theory of Sound." Published by Edward Arnold, London, 1910. A more elementary treatment than Rayleigh's "Theory of Sound."
- Marage.* "Qualités acoustiques de certaines salles pour la voix parlée." Comptes Rendus, Vol. 142, p. 878, 1906. An investigation of the acoustical properties of six halls in Paris.
- Norton, C. L.* "Soundproof Partitions." Insurance Engineering, Vol. 4, p. 180, 1902. An account of experimental tests of the soundproof qualities of materials that are also fireproof.
- Orth, A.* "Die Akustik Grosser Räume mit Specialem Bezug auf Kirchen." Zeitschrift für Bauwesen. Also reprint by Ernst und Korn, Berlin, 1872. Assumes that sound waves behave like light waves. Discusses, with detailed drawings, the paths of sound in the Zion Church in Berlin and the Nicolai Church in Potsdam. Also gives his opinion of the effect of surfaces and materials on sound.
- Rayleigh, Lord.* "Theory of Sound." Two volumes, Macmillan, 1896. The unsurpassed classic in the subject of acoustics. References to architectural acoustics as follows: "Whispering Galleries," Vol. II, § 287. "Passage of Sound Through Fabrics," Vol. II, p. 311. "Resonance in Buildings," Vol. II, § 252.
- Sabine, Wallace C.* "Architectural Acoustics." Engineering Record, 1900, Vol. 1, pp. 349, 376, 400, 426, 450, 477, 503. Published also in book form and in American Architect, Vol. 68, 1900, pp. 3, 19, 35, 43, 59, 75, 83. An important series of articles giving the relation between the time of reverberation in a room, the volume of the room, and absorbing materials present. Gives table of absorbing powers of substances, so that an architect can calculate in advance of construction what the time of reverberation will be.

*Sabine, W. C.* "Architectural Acoustics," *Proc. of the Amer. Acad. of Arts and Sciences*, Vol. XLII, No. 2, June, 1906. A continuation of the previous work, showing the accuracy of musical taste in regard to architectural acoustics and also the variation in reverberation with variation in pitch.

*Sabine, W. C.* "Architectural Acoustics," *Engineering Record*, Vol. 61, pp. 779-781, June 18, 1910. Discusses the case of flow of air in a room and its effect on the acoustics. Concludes that the usual ventilation system in a hall has very little effect.

*Sabine, W. C.* "Architectural Acoustics: The Correction of Acoustical Difficulties." *The Architectural Quarterly* of Harvard University, March, 1912, pp. 3-23. An account of the cures of the acoustical difficulties of a number of audience rooms, also a description of further experiments on the absorbing power of different materials.

*Sabine, W. C.* "Theater Acoustics." *American Architect*, Vol. CIV, pp. 257-279, December 31, 1913. Describes theater with model acoustics. Discusses behavior of sound in a room and shows photographs of sound waves in miniature rooms.

*Sabine, W. C.* "Architectural Acoustics. Building Material and Musical Pitch." *The Brickbuilder*, Vol. 23, pp. 1-6, January, 1914. A continuation of previous work, describing absorbing powers of different materials.

*Sharpe, H. J.* "Reflection of Sound at a Paraboloid." *Camb. Phil. Soc. Proc.*, Vol. 15, pp. 190-197, 1909.

*Stewart, G. W.* "Architectural Acoustics." *Sibley Journal of Engineering*, May, 1903. Published by Cornell University, Ithaca, N. Y. An account of an investigation leading to the cure of the acoustics of Sibley Auditorium.

*Sturmhöfel, A.* "Akustik des Baumeisters." Published by Schuster and Bufleb, Berlin, 1894. An 87-page pamphlet on the acoustics of rooms. Discusses effects of relief work in rooms on sound. Account of experimental work. References to auditoriums.

*Tallant, Hugh.* "Hints on Architectural Acoustics." *The Brickbuilder*, Vol. 19, 1910, pp. 111, 155, 199, 243, 265. A series of articles giving an exposition of the principles of the subject with practical applications.

*Tallant, Hugh.* "Acoustical Design in the Hill Memorial Auditorium, University of Michigan." *The Brickbuilder*, Vol. XXII, p. 169, August, 1913. See also plates 113, 114, 115. A discussion of the acoustical results obtained in this auditorium, a special feature being the action of a huge parabolic reflecting wall surface over the stage.

*Tallant, Hugh.* "Architectural Acoustics. The Effect of a Speaker's Voice in Different Directions." *The Brickbuilder*, Vol. 22, p. 225, October, 1913.

*Taylor, H. O.* "A Direct Method of Finding the Value of Materials as Sound Absorbers." *Physical Review*, Vol. 2 (2), p. 270, October, 1913.

*Tufts, F. L.* "Transmission of Sound Through Porous Materials." *Amer. Journal of Science*, Vol. II, p. 357, 1901. Experimental work leading to the conclusion that sound is transmitted through porous materials in the same proportion that a current of air is.

*Watson, F. R.* "Echoes in an Auditorium." *Physical Review*, Vol. 32, p. 231, 1911. An abstract giving an account of the experiments in the auditorium at the University of Illinois.

*Watson, F. R.* "Inefficiency of Wires as a Means of Curing Defective Acoustics of Auditoriums." *Science*, Vol. 35, p. 833, 1912.

*Watson, F. R.* "The Use of Sounding Boards in an Auditorium." *Physical Review*, Vol. 1 (2), p. 241, 1913. Also a more complete article in *The Brickbuilder*, June, 1913.

*Watson, F. R.* "Air Currents and the Acoustics of Auditoriums." *Engineering Record*, Vol. 67, p. 265, 1913. A detailed account giving theory and experimental work, with application to ventilating systems in auditoriums.

*Watson, F. R.* "Acoustical Effect of Fireproofed Cotton-Flannel Sound Absorbers." *Engineering News*, Vol. 71, p. 261, January 29, 1914. Results of experiments showing that cotton-flannel has practically the same absorbing power after fireproofing as before.

*Weisbach, F.* "Versuche über Schalldurchlässigkeit, Schallreflexion und Schallabsorption." *Annalen der Physik*, Vol. 33, p. 763, 1910.

*Williams, W. M.* "Echo in Albert Hall." *Nature*, Vol. 3, p. 469, 1870-71. Observations on the shape of Albert Hall in London and the echoes set up.

*Editorial Notice.* "The Dresden Laboratory for Architectural Acoustics." *American Architect*, Vol. 102, p. 137, October 16, 1912. States that a laboratory of applied acoustics is authorized in the Dresden (Germany) Technische Hochschule, and that expert advice will be furnished architects and others regarding problems of acoustics of auditoriums.

# PUBLICATIONS OF THE ENGINEERING EXPERIMENT STATION

- Bulletin No. 1.* Tests of Reinforced Concrete Beams, by Arthur N. Talbot. 1904. *None available.*
- Circular No. 1.* High-Speed Tool Steels, by L. P. Breckenridge. 1905. *None available.*
- Bulletin No. 2.* Tests of High-Speed Tool Steels on Cast Iron, by L. P. Breckenridge and Henry B. Dirks. 1905. *None available.*
- Circular No. 2.* Drainage of Earth Roads, by Ira O. Baker. 1906. *None available.*
- Circular No. 3.* Fuel Tests with Illinois Coal (Compiled from tests made by the Technologic Branch of the U. S. G. S., at the St. Louis, Mo., Fuel Testing Plant, 1904-1907), by L. P. Breckenridge and Paul Diserens. 1909. *Thirty cents.*
- Bulletin No. 3.* The Engineering Experiment Station of the University of Illinois, by L. P. Breckenridge. 1906. *None available.*
- Bulletin No. 4.* Tests of Reinforced Concrete Beams, Series of 1905, by Arthur N. Talbot. 1906. *Forty-five cents.*
- Bulletin No. 5.* Resistance of Tubes to Collapse, by Albert P. Carman and M. L. Carr. 1906. *None available.*
- Bulletin No. 6.* Holding Power of Railroad Spikes, by Roy I. Webber. 1906. *None available.*
- Bulletin No. 7.* Fuel Tests with Illinois Coals, by L. P. Breckenridge, S. W. Parr, and Henry B. Dirks. 1906. *None available.*
- Bulletin No. 8.* Tests of Concrete: I, Shear; II, Bond, by Arthur N. Talbot. 1906. *None available.*
- Bulletin No. 9.* An Extension of the Dewey Decimal System of Classification Applied to the Engineering Industries, by L. P. Breckenridge and G. A. Goodenough. 1906. Revised Edition 1912. *Fifty cents.*
- Bulletin No. 10.* Tests of Concrete and Reinforced Concrete Columns. Series of 1906, by Arthur N. Talbot. 1907. *None available.*
- Bulletin No. 11.* The Effect of Scale on the Transmission of Heat Through Locomotive Boiler Tubes, by Edward C. Schmidt and John M. Snodgrass. 1907. *None available.*
- Bulletin No. 12.* Tests of Reinforced Concrete T-Beams, Series of 1906, by Arthur N. Talbot. 1907. *None available.*
- Bulletin No. 13.* An Extension of the Dewey Decimal System of Classification Applied to Architecture and Building, by N. Clifford Ricker. 1907. *None available.*
- Bulletin No. 14.* Tests of Reinforced Concrete Beams, Series of 1906, by Arthur N. Talbot. 1907. *None available.*
- Bulletin No. 15.* How to Burn Illinois Coal Without Smoke, by L. P. Breckenridge. 1908. *Twenty-five cents.*
- Bulletin No. 16.* A Study of Roof Trusses, by N. Clifford Ricker. 1908. *Fifteen cents.*
- Bulletin No. 17.* The Weathering of Coal, by S. W. Parr, N. D. Hamilton, and W. F. Wheeler. 1908. *None available.*
- Bulletin No. 18.* The Strength of Chain Links, by G. A. Goodenough and L. E. Moore. 1908. *Forty cents.*
- Bulletin No. 19.* Comparative Tests of Carbon, Metallized Carbon and Tantalum Filament Lamps, by T. H. Amrine. 1908. *None available.*
- Bulletin No. 20.* Tests of Concrete and Reinforced Concrete Columns, Series of 1907, by Arthur N. Talbot. 1908. *None available.*
- Bulletin No. 21.* Tests of a Liquid Air Plant, by C. S. Hudson and C. M. Garland. 1908. *Fifteen cents.*
- Bulletin No. 22.* Tests of Cast-Iron and Reinforced Concrete Culvert Pipe, by Arthur N. Talbot. 1908. *None available.*
- Bulletin No. 23.* Voids, Settlement, and Weight of Crushed Stone, by Ira O. Baker. 1908. *Fifteen cents.*
- \*Bulletin No. 24.* The Modification of Illinois Coal by Low Temperature Distillation, by S. W. Parr and C. K. Francis. 1908. *Thirty cents.*
- \*Bulletin No. 25.* Lighting Country Homes by Private Electric Plants, by T. H. Amrine. 1908. *Twenty cents.*
- Bulletin No. 26.* High Steam-Pressures in Locomotive Service. A Review of a Report to the Carnegie Institution of Washington, by W. F. M. Goss. 1908. *Twenty-five cents.*
- Bulletin No. 27.* Tests of Brick Columns and Terra Cotta Block Columns, by Arthur N. Talbot and Duff A. Abrams. 1909. *Twenty-five cents.*
- Bulletin No. 28.* A Test of Three Large Reinforced Concrete Beams, by Arthur N. Talbot. 1909. *Fifteen cents.*
- Bulletin No. 29.* Tests of Reinforced Concrete Beams: Resistance to Web Stresses, Series of 1907 and 1908, by Arthur N. Talbot. 1909. *Forty-five cents.*
- \*Bulletin No. 30.* On the Rate of Formation of Carbon Monoxide in Gas Producers, by J. K. Clement, L. H. Adams, and C. N. Haskins. 1909. *Twenty-five cents.*
- \*Bulletin No. 31.* Fuel Tests with House-heating Boilers, by J. M. Snodgrass. 1909. *Fifty-five cents.*
- Bulletin No. 32.* The Occluded Gases in Coal, by S. W. Parr and Perry Barker. 1909. *Fifteen cents.*
- Bulletin No. 33.* Tests of Tungsten Lamps, by T. H. Amrine and A. Guell. 1909. *Twenty cents.*
- \*Bulletin No. 34.* Tests of Two Types of Tile Roof Furnaces under a Water-Tube Boiler, by J. M. Snodgrass. 1909. *Fifteen cents.*
- Bulletin No. 35.* A Study of Base and Bearing Plates for Columns and Beams, by N. Clifford Ricker. 1909. *Twenty cents.*

\*A limited number of copies of those bulletins which are starred are available for free distribution.



## PUBLICATIONS OF THE ENGINEERING EXPERIMENT STATION

- \**Bulletin No. 36.* The Thermal Conductivity of Fire-Clay at High Temperatures, by J. K. Clement and W. L. Egy. 1909. *Twenty cents.*
- Bulletin No. 37.* Unit Coal and the Composition of Coal Ash, by S. W. Parr and W. F. Wheeler. 1909. *Thirty-five cents.*
- \**Bulletin No. 38.* The Weathering of Coal, by S. W. Parr and W. F. Wheeler. 1909. *Twenty-five cents.*
- \**Bulletin No. 39.* Tests of Washed Grades of Illinois Coal, by C. S. McGovney. 1909. *Seventy-five cents.*
- Bulletin No. 40.* A Study in Heat Transmission, by J. K. Clement and C. M. Garland. 1910. *Ten cents.*
- \**Bulletin No. 41.* Tests of Timber Beams, by Arthur N. Talbot. 1910. *Twenty cents.*
- \**Bulletin No. 42.* The Effect of Keyways on the Strength of Shafts, by Herbert F. Moore. 1910. *Ten cents.*
- Bulletin No. 43.* Freight Train Resistance, by Edward C. Schmidt. 1910. *Seventy-five cents.*
- \**Bulletin No. 44.* An Investigation of Built-up Columns Under Load, by Arthur N. Talbot and Herbert F. Moore. 1911. *Thirty-five cents.*
- \**Bulletin No. 45.* The Strength of Oxyacetylene Welds in Steel, by Herbert L. Whittemore. 1911. *Thirty-five cents.*
- Bulletin No. 46.* The Spontaneous Combustion of Coal, by S. W. Parr and F. W. Kressmann. 1911. *Forty-five cents.*
- \**Bulletin No. 47.* Magnetic Properties of Heusler Alloys, by Edward B. Stephenson. 1911. *Twenty-five cents.*
- \**Bulletin No. 48.* Resistance to Flow Through Locomotive Water Columns, by Arthur N. Talbot and Melvin L. Enger. 1911. *Forty cents.*
- \**Bulletin No. 49.* Tests of Nickel-Steel Riveted Joints, by Arthur N. Talbot and Herbert F. Moore. 1911. *Thirty cents.*
- \**Bulletin No. 50.* Tests of a Suction Gas Producer, by C. M. Garland and A. P. Kratz. 1912. *Fifty cents.*
- \**Bulletin No. 51.* Street Lighting, by J. M. Bryant and H. G. Hake. 1912. *Thirty-five cents.*
- \**Bulletin No. 52.* An Investigation of the Strength of Rolled Zinc, by Herbert F. Moore. 1912. *Fifteen cents.*
- \**Bulletin No. 53.* Inductance of Coils, by Morgan Brooks and H. M. Turner. 1912. *Forty cents.*
- Bulletin No. 54.* Mechanical Stresses in Transmission Lines, by A. Guell. 1912. *Twenty cents.*
- \**Bulletin No. 55.* Starting Currents of Transformers, with Special Reference to Transformers with Silicon Steel Cores, by Trygve D. Yensen. 1912. *Twenty cents.*
- \**Bulletin No. 56.* Tests of Columns: An Investigation of the Value of Concrete as Reinforcement for Structural Steel Columns, by Arthur N. Talbot and Arthur R. Lord. 1912. *Twenty-five cents.*
- \**Bulletin No. 57.* Superheated Steam in Locomotive Service. A Review of Publication No. 127 of the Carnegie Institution of Washington, by W. F. M. Goss. 1912. *Forty cents.*
- \**Bulletin No. 58.* A New Analysis of the Cylinder Performance of Reciprocating Engines, by J. Paul Clayton. 1912. *Sixty cents.*
- \**Bulletin No. 59.* The Effect of Cold Weather Upon Train Resistance and Tonnage Rating, by Edward C. Schmidt and F. W. Marquis. 1912. *Twenty cents.*
- \**Bulletin No. 60.* The Coking of Coal at Low Temperatures, with a Preliminary Study of the By-Products, by S. W. Parr and H. L. Olin. 1912. *Twenty-five cents.*
- \**Bulletin No. 61.* Characteristics and Limitations of the Series Transformer, by A. R. Anderson and H. R. Woodrow. 1913. *Twenty-five cents.*
- Bulletin No. 62.* The Electron Theory of Magnetism, by Elmer H. Williams. 1913. *Thirty-five cents.*
- \**Bulletin No. 63.* Entropy-Temperature and Transmission Diagrams for Air, by C. R. Richards. 1913. *Twenty-five cents.*
- \**Bulletin No. 64.* Tests of Reinforced Concrete Buildings Under Load, by Arthur N. Talbot and Willis A. Slater. 1913. *Fifty cents.*
- \**Bulletin No. 65.* The Steam Consumption of Locomotive Engines from the Indicator Diagrams, by J. Paul Clayton. 1913. *Forty cents.*
- Bulletin No. 66.* The Properties of Saturated and Superheated Ammonia Vapor, by G. A. Goodenough and William Earl Mosher. 1913. *Fifty cents.*
- Bulletin No. 67.* Reinforced Concrete Wall Footings and Column Footings, by Arthur N. Talbot. 1913. *Fifty cents.*
- \**Bulletin No. 68.* Strength of I-Beams in Flexure, by Herbert F. Moore. 1913. *Twenty cents.*
- \**Bulletin No. 69.* Coal Washing in Illinois, by F. C. Lincoln. 1913. *Fifty cents.*
- \**Bulletin No. 70.* The Mortar-Making Qualities of Illinois Sands, by C. C. Wiley. 1913. *Twenty cents.*
- \**Bulletin No. 71.* Tests of Bond between Concrete and Steel, by Duff A. Abrams. 1914. *One dollar.*
- \**Bulletin No. 72.* Magnetic and Other Properties of Electrolytic Iron Melted in Vacuo, by Trygve D. Yensen. 1914. *Forty cents.*
- \**Bulletin No. 73.* Acoustics of Auditoriums, by F. R. Watson. 1914. *Twenty cents.*

\*A limited number of copies of those bulletins which are starred are available for free distribution.



**THE UNIVERSITY OF ILLINOIS**  
**THE STATE UNIVERSITY**  
**Urbana**

EDMUND J. JAMES, Ph. D., LL. D., President

---

**The University includes the following departments:**

**The Graduate School**

**The College of Liberal Arts and Sciences** (Ancient and Modern Languages and Literatures; History, Economics and Accountancy; Political Science, Sociology; Philosophy, Psychology, Education; Mathematics; Astronomy; Geology; Physics; Chemistry; Botany, Zoology, Entomology; Physiology; Art and Design; Ceramics)

**The College of Engineering** (Architecture; Architectural, Civil, Electrical, Mechanical, Mining, Municipal and Sanitary, and Railway Engineering)

**The College of Agriculture** (Agronomy; Animal Husbandry; Dairy Husbandry; Horticulture and Landscape Gardening; Veterinary Science; Agricultural Extension; Teachers' Course; Household Science)

**The College of Law** (Three years' course)

**The School of Education**

**The Courses in Business** (General Business; Banking; Accountancy; Railway Administration; Insurance)

**The Course in Journalism**

**The Courses in Chemistry and Chemical Engineering**

**The Courses in Ceramics and Ceramic Engineering**

**The School of Railway Engineering and Administration**

**The School of Music** (four years' course)

**The School of Library Science** (two years' course)

**The College of Medicine** (in Chicago)

**The College of Dentistry** (in Chicago)

**The School of Pharmacy** (In Chicago; Ph. G. and Ph. C. courses)

**The Summer Session** (eight weeks)

**Experiment Stations:** U. S. Agricultural Experiment Station; Engineering Experiment Station; State Laboratory of Natural History; State Entomologist's Office; Biological Experiment Station on Illinois River; State Water Survey; State Geological Survey; Mine Rescue Station

The *library collections* contain (May 1, 1914), 295,000 volumes, including the library of the State Laboratory of Natural History, the Quine Medical Library and the library of the School of Pharmacy.

**For catalogs and information address**

**THE REGISTRAR**  
*Urbana, Illinois*

